



Qmax[®] Select

"Same Qmax Pump you have
come to love, with an easier
way of ordering it."

Qmax[®] Performance

Generates NFPA 1901 rated flows up to 2,250 gpm (8,515 lpm) from draft

Performance range from 0-3,000 gpm (12,000 lpm) (based upon available horsepower and water sources)

Low Friction Losses allow up to 1,500 gpm (6,000 lpm) on 3" body openings

Large Suction Inlets and Full Flow Waterways cut friction loss and deliver maximum pressure

Strength in Design, a one piece upper pump body minimizes plumbing leaks and makes maintenance and service easy

Hale's auto-lube system force feed lubrication, eliminating the needs for a second packing or seal

Low Friction Losses allow up to 2,600 gpm (9,800 lpm) on 4" body openings

Dual Cutwaters provide smooth waterway delivery to the pump with no twist turns or restrictions that add turbulence

The Qmax Select Advantage



Product Simplification

Qmax Select offers our most popular configurations specified by the industry. By reducing the complexity during the ordering process it is easier to do business



Pricing Advantage

Select program participation provides a 5% lower price point verses all non-Qmax Select (fully configured pump) orders



Improved Lead Time

Lead times are guaranteed to 6 weeks when choosing Select options

Qmax Select Promotion (valid through 2018)

Hale will provide a 5% credit if we do not meet the 6 week guaranteed lead-time on Qmax Select Pump orders.

