Hale Products, Inc. Service Bulletins						
Bulletin#:	E: SB-91 Revision#: A Date: 10/8/06					
Product Type Covered: Hale Pump X Hurst Tool Lukas Tool Product Covered:						
SVS - Valves						
Problem S	tatement	:				
SVS Tori		es require lubr	ication to work	properly and	to maintain	
Written by:	Mark Coley, Product		Date:	10/8/06	10/8/06	
Approved by: Mike I		Laskaris			_	
Product Manager:		Mark Coley				
Customer Serv	vice Designe	ee:				

Body of the Bulletin

The SVS Torrent Valve is designed to use grease. The recommended types of grease are outlined below and can be found in Section 4, Routine Maintenance, of the SVS Installation and Service Manual, Hale p/n: 029-0020-90-0. Lubrication intervals vary dependent upon operating conditions (amount of usage, water conditions, etc.). When SVS Torrent Valves are inadequately lubricated it shortens the life span of smooth operation and causes unnecessary "downtime." The warranty on the SVS Torrent Valve is ten (10) years workmanship and two (2) years on the seals. FAILURE TO PROPERLY MAINTAIN and LUBRICATE VALVES COULD RESULT IN WARRANTY DENIAL.

LUBRICANTS:

Use one of the following lubricants. DO NO substitute other lubricants.

• **Never-Seez** - White Food Grade with PTFE, manufactured by:

Bostik Findley, Inc. 211 Boston Street

Middleton, MA. 01949-2128

Web: www.bostikfindley-us.com

• White Knight tm - Food Grade Anti-Seize Compound, manufactured by:

Jet Lube Inc.

4849 Homestead Road

Suite 500

Houston, TX 77028 Web: <u>www.jetlube.com</u>

• Anti-Seize tm - manufactured by:

U.S. Valve Service & Training, Inc.

11875 West Little York

Suite 502

Houston, TX. 77041

Web: <u>www.usvalveservices.com/prod7.htm</u>

Also see SVS Torrent Installation and Service Maintenance Manual, Hale p/n: 029-0020-90-0, Section 4 "Routine Maintenance" for additional information.