



Seat Belt Warning Indicator large

STYLE

This module allows the operator to identify non-belted parties at a glance. It communicates with the SBW module Via the J1939 CAN bus.

Features

The Seat Belt Warning display (p/n 118551) is capable of showing the seat status of up to 10 seats while the Seat Belt Warning display (p/n 119375) is capable of showing the seat status of up to 6 seats, both with individual (red and green) seat status LEDs.

Applications/Solutions

- Fire OEMs
- Firefighting - Airport (ARFF)
- Firefighting - Industrial
- Firefighting - Structural
- Firefighting - Wildland Forestry

- 12 seat position indicators



Specifications

Country of Manufacture	US
Width	5.25" (133.35 mm)
Height	3.25" (82.55 mm)
Depth	0.9" (22.86 mm)
Volts	+9 VDC ... +32 VDC
Amperage	25 ... 75 mA (13.8 VDC)
Can Specification	SAE J1939 Proprietary, 250 Kbits/second
Enviromental Range	IP 42

Seat Belt Warning Indicator large

STYLE

Temperature range

- -40°C...+85°C

Electrical protection

- Internal thermal fuse
- Reverse voltage protection
- CAN buses protected to 24V
- ESD voltage protected to SAE J1113 specification for heavy duty trucks (24V)
- Transient voltage protected to SAE J1113 specification for heavy duty trucks (24V)