

SmartATP

STYLE

SmartATP is an intelligent, automated around-the-pump foam system that delivers high-volume, precise foam for every fire situation. Eliminating the problems with traditional manual systems, the SmartATP automatically regulates the foam ratio control valve, eliminating the opportunity for operator error and wasted foam.

Features

- One Button Press Operation easily delivers precise foam for every situation
- Integrated tutorials makes calibration and other programming easy to use
- Auto-Flush capability automatically flushes system when switching foam types
- Plain text messaging provide operators with critical information, diagnostics, or system errors
- AutoFill capable: allows intake connection from a pressurized source which then maintains a consistent water tank level automatically without water hammer
- Optional Dual Tank installation kit allowing both A and B foam
- OEM installation kits includes the necessary valves, solenoids, and couplings for installation
- Available fully assembled with a new Hale pump or as an independent kit
- Ability to adjust foam ratio from 0.1% to 10%
- Available at maximum foam flow capacities of either 125 gpm (473 lpm) or 225 gpm (851 lpm)
- In excess of 3500 gpm of 6% Foam and Water solution at 150 Psi (10 bar)
- Multilingual language input

Applications/Solutions

- Firefighting Airport (ARFF)
- Firefighting Industrial
- Firefighting Structural
- Firefighting Wildland Forestry
- Petro-Chemical



Specifications

Warranty	WARRANTY
Material	Bronze Eductor,
	Stainless Steel Valve
Brand	SmartFoam
Can Specification	J1939, 250kbit/s

Copyright 2024 Hale. All rights reserved. No portion of this can be reproduced without the express written consent of the Hale. (04/24)

SmartATP

STYLE



SmartATP

STYLE

Flow Rate:

- 125 GPM or
- 225 GPM

Voltage:

- 12V or
- 24V

Number of Flowmeters:

• Up to 10

Control Valves:

- Electric or
- Air